





SCHEMATIC





PCB LAYOUT

**RoHS
Compliance**



CAP FOR UG



7	BALL	STEEL	2					
5	CONTACT	BRASS	1	Ag PLATED	6	SPRING	STEEL WIRE	2
3	TERMINAL	BRASS	7	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1
1	FRAME	S P C C	1	PLATING-CHROME	2	KNOB	P O M	1
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY

ISSUED

SPECIFICATION

TITLE: SLIDE SWITCH (1P6T)

RATING: DC 30V 0.3A

CONTACT RESISTANCE: 30mΩ max.

INSULATION RESISTANCE: 500MΩ at 500V DC

WITHSTAND VOLTAGE: AC 500V for 1 minute

OPERATION FORCE: REFER ATTACH SPECIFICATION

SWITCHING LIFE: 10K cycles min.

MODEL NO: SS-16F03

TOLERANCE

UP TO 1.0:±0.1

1.0 TO 10.0:±0.2

OVER 10.0:±0.3

UNIT: MM

SCALE: 2:1

VERSION: 01

DRWG NO:

DWN.

CHK'D.

APPD.

BY:

DATE: 04-JUN-1999

VIMEX
INTERNATIONAL CORPORATION

