



800-227-0075

http://www.vimex.com

# Part Number System

T 8 4 0 1 P - S - E - Q - E - S - T 1 - 2

Switch Function (4PDT)				Actuator		Bushing		Contact	Epoxy Seal	Support Bracket Type		Actuator Cap		Cap Color		
Model No.	Switching Position			S	10.41	E	(STD)	8.89	Q	(none)	(none)	T1	10.29 actuator S	0	Clear	
T8401P	ON	none	ON	T	5.08	M	non-thrd	8.89	R	E	S	snap-in type	T2	7.28 actuator T	1	White
T8403P	ON	none	(ON)	X	13.97	K	metric	8.89	G					2	Black	
T8405P	ON	OFF	ON	W	21.34	F		7.10	K					3	Red	
T8407P	(ON)	OFF	(ON)	V	16.26	N	non-thrd	7.10						4	Yellow	
T8409P	ON	OFF	(ON)	Flatted Toggle		G		7.52						5	Blue	
Term Comm	2-3,5-6 8-9,11-12	open	2-1,5-4 8-7,11-10	U	11.43	G1	non-thrd	7.52						6	Green	
				U1	7.20	H		8.00						7	Orange	
				Locking Lever		H1	non-thrd	8.00								
				LK	Round	J	(long)	9.60								
				LK1	Flat top	J1	non-thrd	9.60								
						L	splash-prf	7.47								
						none										
						No code if LK/LK1 actuator unless splash proof or non-thread chosen										

See following pages for details

Page: 1				Date: 2003-12-17				Description: Build a part number.			
of: 5				Revision: 1.0				P/N T8401P			



800-227-0075

http://www.vimex.com

# Part Number System

Actuator Options				
S (standard)	T (standard)	X (long)	W (long)	V (long)
Flatted Actuators (only available with 'H' or 'H1' or 'H2' bushing)			Locking Lever	
U (standard)	U1 (short)	LK (round top)	LK1 (flat top)	
<p>Bushing option code not required unless 'L' splashproof bushing is ordered</p>			<p>Bushing option code not required unless:            (1) 'L' splashproof bushing ordered (i.e. LKL or LK1L)            (2) non-thread bushing required choose bushing code 'N' (i.e. LKN or LK1N)            Locking Levers ONLY available with ON-ON or ON-OFF-ON action.</p>	

Page:	2	Date:	2003-12-17	Description:	Build a part number.
of:	5	Revision:	1.0	P/N	<b>T8401P</b>



800-227-0075

http://www.vimex.com

# Part Number System

## Bushing Option

E threaded (standard) M non-thread	F threaded N non-thread	G threaded (standard) G1 non-thread	H threaded (standard) H1 non-thread H2 Metric	J threaded (standard) J1 non-thread	K Metric

## Splash proof Solution

### L

--	--	--	--

Description:

Build a part number.

Page:	3	Date:	2003-12-17
of:	5	Revision:	1.0

P/N

T8401P



800-227-0075

http://www.vimex.com

# Part Number System

## Panel Mounting

1/4" Bushing		Metric Bushing		
<p>keyway</p>	<p>flatted D</p>	<p>with locking ring</p>	<p>keyway</p>	<p>with locking ring</p>

## Contact Material Options

Code	Contact Material	Terminal Material	Rating
Q	Silver plated	Silver plated	5A @ 120VAC or 28VDC; 2A @ 250VAC
R	Gold plated over nickel plated	Gold plated over nickel plated	0.4VA max. @ 20VAC or VDC max.
G	Gold plated over silver plated	Gold plated over silver plated	0.4VA max. @ 20VAC or VDC max. <i>or</i> 5A @ 120VAC or 28VDC; 2A @ 250VAC
K	Gold plated over nickel plated	Tin-lead over nickel plated	0.4VA max. @ 20VAC or VDC max.

Page:	4	Date:	2003-12-17	Description:	Build a part number.
of:	5	Revision:	1.0	P/N	<b>T8401P</b>



800-227-0075

http://www.vimex.com

# Part Number System

Toggle Cap Option		Toggle Cap Color Option	
T1 (for 'S' actuator only)	T2 (for 'T' actuator only)	Code	Color
<p>.405 10.29 Material Vinyl</p>	<p>.287 7.29 Material Vinyl</p>	0	Transparent
		1	White
		2	Black
		3	Red
		4	Yellow
		5	Blue
		6	Green
		7	Orange

Hardware					
1/4-40NS hex (standard)	1/4-40NS DRESS NUT	Metric hex	1/4" & M6 Lock Ring	Flatted bush Lock Ring	1/4" & M6 Lock Washer
<p>.312 7.92 1/4-40NS .062 1.57</p>	<p>.352 8.94 1/4-40NS .372 DIA 9.45 .118 3.00</p>	<p>.409 10.39 M6P 0.75 THD .354 8.99 .062 1.57</p>	<p>.029 0.74 .468 DIA 11.89 .065 1.65</p>	<p>.029 0.74 .468 DIA 11.89 .065 1.65</p>	<p>.408 DIA 10.36 .018 0.46 THK</p>

Page:	5	Date:	2003-12-17	Description:	Build a part number.
of:	5	Revision:	1.0	P/N	T8401P