







Technical drawing of a square flange. The drawing shows a square flange with a central circular hole. The overall width and height are 8.2 and 6.4 respectively. The central hole has a diameter of 6.2. The flange has four mounting holes, each with a diameter of 0.9. The distance between the centers of the mounting holes is 0.2. The flange has a thickness of 0.7. The drawing includes callouts 3 and 4 pointing to specific features.




BY: <i>Lee</i>		
DATE: 28-Jun-2012		

RoHS
Compliance



SCHEMATIC



PCB LAYOUT

5	CONTACT	S U S	1	Ag PLATED					
3	TERMINAL	BRASS	4	Ag PLATED	4	COVER	S U S	1	
1	FRAME	NYLON 46	1	BLACK	2	KNOB	NYLON 46	1	BLACK
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY	REMARKS

ISSUED	SPECIFICATION	TITLE: TACT SWITCH				
	RATING: DC 12V 50mA	MODEL NO: TC-12020A-00-P-E				
	CONTACT RESISTANCE: 100mΩ Max.					
	INSULATION RESISTANCE: 100MΩ at 500V DC	TOLERANCE	UNIT: MM	DWN.	Jm	
	WITHSTAND VOLTAGE: AC 250V for 1 minute.	UP TO 1.0:±0.1	SCALE: 5:1	CHK"D.	Jm	
	OPERATION FORCE: REFER ATTACH SPECIFICATION	1.0 TO 10.0:±0.2	VERSION: 02	APPD.	Jm	
	SWITCHING LIFE: 100k Cycles Min.	OVER 10.0:±0.3	DRWG NO:			

BY: Jm
DATE: 28-Jun-2012

VIMEX
INTERNATIONAL CORPORATION

